



Toll Free (800) 676-6307
www.con-cretewerks.com

SECTION 2: HAZARDS IDENTIFICATION

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: B

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES..

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATION OF VAPOR. EYES: INJURY IF UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

CARCINOGENICITY

OSHA: NO NTP: yes IARC: yes

ADDITIONAL CARCINOGENICITY INFORMATION:

crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



Toll Free (800) 676-6307
www.con-cretewerks.com

<u>INGREDIENT</u> <u>WEIGHT %</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>
MODIFIED DIGLYCIDYL ETHER OF				
BISPHENOL A	25068-38-6	NONE	NONE	NONE
Alky Quartenary Ammonium Bentonite	68953-58-2	50mg/m3	10mg/m3	20mg/m3
*crystalline silica (as a component of Alky Quarternary Ammonium Bentonite)				
(<0.5%)	14807-60-7	10mg/m3	.1mg/m3	.1mg/m3
Talc	14807-96-6	20mg/m3	20mg/m3	20mg/m3
*crystalline silica (as a component of talc) (<1.0%)	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3
LIMESTONE	1317-65-3	15mg/m3	5MG/M3	NONE
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE

SECTION 3 NOTES: *** indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 4: FIRST AID MEASURES

EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE CONSULT WITH A PHYSICIAN.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.



Toll Free (800) 676-6307
www.con-cretewerks.com

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: not available
(% by volume) LOWER: not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS



Toll Free (800) 676-6307
www.con-cretewerks.com

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR

VENTILATION :

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: VISCOUS PASTE – NEGLIGIBLE ODOR

BOILING POINT OR RANGE: 200 TO 401F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 1.6



Toll Free (800) 676-6307
www.con-cretewerks.com

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO₂, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component CAS# 68953-58-2: Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen. Oral LD50 (rat) > 8g/mg

Component CAS# 14807-96-6: Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

Component Limestone: LD50 Oral (rat) = 6450 mg/kg. This product contains greater than 0.1% crystalline silica which is listed as a group I carcinogen by IARC, a known carcinogen by NTP, OSHA and as A2 suspected human carcinogen by ACGIH



Toll Free (800) 676-6307
www.con-cretewerks.com

Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

SECTION 12: ECOLOGICAL INFORMATION

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component CAS# 68953-58-2: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

Component CAS# 14807-96-6: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

Component Limestone: inert material

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD₂ 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:.

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) , 9, PGIII,

SECTION 15: REGULATORY INFORMATION



Toll Free (800) 676-6307
www.con-cretewerks.com

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list,; is on the PA Right to Know List;

Component CAS# 68953-58-2: may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance. Component is on the DSL, EINECS, AICS, ENCS, ECL, PICCS and CLECS lists

Component CAS# 14807-96-6 may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Component Limestone: TSCA listed. Canada Exempt, naturally occurring Substance. EINECS, ECL, ENCS, CIES, PICCS listed. This product contains trace amounts of chemicals known to the state of California to cause cancer or reproductive effects.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.



Toll Free (800) 676-6307
www.con-cretewerks.com



Toll Free (800) 676-6307
www.con-cretewerks.com



Toll Free (800) 676-6307
www.con-cretewerks.com

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: NP818 PART B

PRODUCT CODES: 818 B

MANUFACTURER: National Polymers Inc.

STREET ADDRESS: 9 Guttman Avenue

CITY, STATE, ZIP: Charleroi, Pa. 15022

INFORMATION PHONE: 724-483-9300

EMERGENCY PHONE: Chemtrec 800-424-9300

FAX PHONE: 724-483-9306

PREPARED BY: Harry Jackson

DATE REVISED: 1/2/13

SECTION 2: HAZARDS IDENTIFICATION

HMS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES:

WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN:

WILL CAUSE BURNS TO THE SKIN



Toll Free (800) 676-6307
www.con-cretewerks.com

INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

CARCINOGENICITY

OSHA: NO NTP: yes IARC: yes

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION

OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen. Product may contain ethyl benzene as a component of xylene (IARC 2B). Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u> <u>WEIGHT %</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>
TRIETHYLENE TETRAMINE	112-24-3	NONE	NONE	NONE
Dimer/tofa, reaction products with Teta	68082-29-1	NONE	NONE	NONE
HYDROCARBON RESIN	NON-HAZARDOUS	NONE	NONE	NONE
*Naphthalene <0.06	91-20-3	10ppm	10ppm	NONE
HYDROXY MODIFIED RESIN	NON-HAZARDOUS	NONE	NONE	NONE
*Xylene 1	1330-20-7	100PPM	100PPM	150PPM



Toll Free (800) 676-6307
www.con-cretewerks.com

*ethyl benzene (as a component of xylene) <0.2	100-41-4	100ppm	100ppm	125ppm
Alky Quarternary Ammonium Bentonite	68953-58-2	50mg/m3	10mg/m3	20mg/m3
*crystalline silica (as a component of Alky Quarternary Ammonium Bentonite) (<0.5%)	14807-60-7	10mg/m3	.1mg/m3	.1mg/m3
Talc	14807-96-6	20mg/m3	20mg/m3	20mg/m3
*crystalline silica (as a component of talc) (<1.0%)	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3
LIMESTONE	1317-65-3	15mg/m3	5MG/M3	NONE
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE
*CARBON <1.0	1333-86-4	3.5PPM	3.4PPM	NONE
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3

SECTION 3 NOTES:

Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

XYLENE ACGIH STEL=150PPM

SECTION 4: FIRST AID MEASURES

EYES:

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.



Toll Free (800) 676-6307
www.con-cretewerks.com

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: not available
(% by volume) LOWER: not available

FLASH POINT: 200+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

SECTION 7: HANDLING AND STORAGE



Toll Free (800) 676-6307
www.con-cretewerks.com

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:



Toll Free (800) 676-6307
www.con-cretewerks.com

VISCOUS PASTE WITH AMINE ODOR

BOILING POINT OR RANGE: 279 TO 401F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 1.5

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO₂, NOX

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

Component CAS# 68953-58-2: Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen. Oral LD₅₀ (rat) > 8g/mg



Toll Free (800) 676-6307
www.con-cretewerks.com

Component CAS# 14807-96-6: Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

Component Limestone: LD50 Oral (rat) = 6450 mg/kg. This product contains greater than 0.1% crystalline silica which is listed as a group I carcinogen by IARC, a known carcinogen by NTP, OSHA and as A2 suspected human carcinogen by ACGIH

Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

Component CAS# 68082-29-1 and CAS# 112-24-3: Acute Oral Toxicity LD50 (rat) >2000 mg/kg (estimate); Acute Dermal Toxicity LD50 (rabbit) >2000 mg/kg (estimate); Component has caused allergic sensitization in humans.

Component Xylene: Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene, and toluene. Ethyl benzene has shown limited evidence of a carcinogenic effect.

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

SECTION 12: ECOLOGICAL INFORMATION

Component CAS# 68953-58-2: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

Component CAS# 14807-96-6: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

Component Limestone: inert material

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD₂ 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

Component Xylene: Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidizes rapidly by photo-chemical reactions in air.

Component Titanium Dioxide: *Pimephales promelas* (fathead minnow) < 1000 mg/l @ 96h LC50; *Pseudokirchneriella subcapitata* (green algae) 61 mg/l @ 72h EC50; *Daphnia magna* (water flea) > 1000 mg/l @ 48h EC50



Toll Free (800) 676-6307
www.con-cretewerks.com

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/IMDG: Not Regulated

SECTION 15: REGULATORY INFORMATION

Component CAS# 68953-58-2: may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance. Component is on the DSL, EINECS, AICS, ENCS, ECL, PICCS and CLECS lists

Component CAS# 14807-96-6 may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Component Limestone: TSCA listed. Canada Exempt, naturally occurring Substance. EINECS, ECL, ENCS, CIES, PICCS listed. This product contains trace amounts of chemicals known to the state of California to cause cancer or reproductive effects.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 68082-29-1 and CAS# 112-24-3 are on the TSCA list. OSHA Hazard class – irritant, sensitizer. On the Canadian DSL, on the EINECS master inventory

Component HYDROCARBON RESIN: Component contains 0.01-0.06 wt% Naphthalene CAS# 91-20-3 with a CERCLA RQ of 100 pounds. Component is on the TSCA list and Canadian DSL list. Component does not contain any reportable chemicals above the de minimus level for section 313. Component is not hazardous as defined by CFR 1910.1200 or Title III section 312/313 of the superfund amendment. Naphthalene is known to the state of California to cause cancer. Naphthalene is on the Pennsylvania, Massachusetts and New Jersey right to know lists.

Component HYDROXY MODIFIED RESIN.: Component is not hazardous as defined by CFR 1910.1200 and under the provisions of Title III Section 311/312 of the Superfund amendments and Reauthorization Act. Component is on the TSCA list..



Toll Free (800) 676-6307
www.con-cretewerks.com

Component Xylene: Xylene contains EPCRA section 313 chemicals subject to the reporting requirements of the emergency planning and community right to know act of 1968. (Maximum wt % for components of xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethyl Benzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%.. Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Philippines inventory lists and on the Massachusetts, New Jersey, Pennsylvania right to know lists Ethyl Benzene a component of xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

Component Carbon: Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List.

Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.