

PRECAUTIONS:

Flammable Liquid (Flash point < 20° F). Keep away from open flame and heat. Do not smoke. Avoid direct contact. Skin and eye irritation may occur.

Use in well-ventilated area. Inhalation of vapors may cause breathing difficulties.

KEEP OUT OF REACH OF CHILDREN.

Recommended for exterior use only.

FIRST AID:

Eye contact: Move victim from exposure source. Flush eyes with water for 10-15 minutes.

Skin: Remove contaminated clothing. Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Move victim to fresh air immediately. Contact physician if breathing is difficult.

FOR CHEMICAL EMERGENCY

Spill, Leak, Fire, Exposure or Accident

CALL INFOTRAC- Day or Night

800-535-5053

OUTSIDE THE UNITED STATES CALL COLLECT 1-352-323-3500

HMIS: Health - 2 Flammability - 3 Reactivity - 0

Please refer to msds & technical data sheet prior to use of this product.

ATTENTION:

This container is hazardous when empty. Empty containers retain product residues (vapor and liquid). All labeled precautions must be observed. Do not re-use empty container for any purpose until commercially cleaned or reconditioned. Store empty container away from heat, sparks, and flame. Dispose of empty container according to state and federal laws. Clean up with Xylene.

WARRANTY:

Surface Koatings, Inc. warrants our products to be of good quality, free of defects and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after Surface Koatings, Inc. has shipped the products, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will Surface Koatings, Inc. be liable for a consequential damage to anyone in excess of the purchase price of the products.

SHelf LIFE:

Up to two years in unopened container stored at room temperature.



RE-JUVENATE



SEALER AID

Directions for use will vary with product use.

PLEASE NOTE:

It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and inadequate film formation or performance expectations may be limited.



FOR PROFESSIONAL USE ONLY!
VOC CONTENT: EXEMPT
DOT: Paint Related Material, 3, UN1263, PG II

Solids	0%
Drying Time	1.85 (Evaporation Rate)
Re-Coat Time	N/A
Foot Traffic	N/A
Wheel Traffic	N/A
Application Temp	50 °F - 80 °F
Wet Appearance	Clear
Dry Appearance	N/A
VOC Content	Exempt
Blush Resistance	N/A
Solvent Resistance	N/A
Concrete Adhesion	N/A

*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

www.con-cretewerks.com

Made in the USA