

Refer to sealer label for surface prep, application instructions and coverage rates.

**MIXING:**

**For Satin Finish**

Mix contents of one pint container with exactly 5 gallons of approved, solvent based acrylic sealer for a Satin Finish. Keep material mixed well during sealer application process.

**For Matte Finish**

Mix contents of two pint containers with exactly 5 gallons of approved, solvent based acrylic sealer for a Matte Finish. Keep material mixed well during sealer application process.

MIX WELL PRIOR TO APPLICATION!

**FOR CHEMICAL EMERGENCY**

Spill, Leak, Fire, Exposure or Accident

CALL INFOTRAC: Day or Night

800-535-5053

OUTSIDE THE UNITED STATES CALL COLLECT 1-352-323-3500

HMIS: Health - 2 Flammability - 3 Reactivity - 0

FOR PROFESSIONAL USE ONLY!

DO NOT THIN!

VOC CONTENT: Contains no VOC's

DOT: Consumer Commodity ORM-D

Please refer to msds & technical data sheet prior to use of this product.

## Addition for Stamp Seal 25/30



# MATTE

**PLEASE NOTE:**

It is always recommended to test material in a small, inconspicuous area (one the same concrete substrate) for desired results prior to entire application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc.

**CLEAN-UP:**

Use xylene/xylol or MEK. Do not use alcohols.

**SAFETY PRECAUTIONS:**

Use only in well ventilated areas. Use respirators. Protect eyes and skin from direct contact.

**FIRST AID: INGESTION:**

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention immediately. **INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately. **EYES:** Do not rub. Flush eyes with plenty of water for 15 minutes while holding eyelids open. If irritation persists, get medical attention immediately. **SKIN:** Wash with soap and water. Remove contaminated clothing and shoes. Do not reuse until cleaned. If persistent irritation occurs, get medical attention.

**WARRANTY:**

Surface Koatings, Inc. warrants our products to be of good quality, free of defects and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after Surface Koatings, Inc. has shipped the products, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will Surface Koatings, Inc. be liable for a consequential damage to anyone in excess of the purchase price of the products.

**SHELF LIFE:**

Up to one year in unopened container stored at room temperature.

[www.con-cretewerks.com](http://www.con-cretewerks.com)

Made in the USA